




Timken BEARING MFG.CORP

6 mm x 19 mm x 6 mm NTN 626ZZ deep groove ball bearings



Bearing No. 626ZZ

626ZZ Bearing 2D drawings and 3D CAD models

Size	6x19x6 mm
Bore Diameter	6 mm
Outer Diameter	19 mm
Width	6 mm
d	6 mm
D	19 mm
B	6 mm
C	6 mm
r min.	0,3 mm
da min.	8 mm
da max	9,5 mm
Da max.	17 mm
ra max.	0,3 mm
Weight	9,2 Kg
Basic dynamic load rating (C)	2,34 kN
Basic static load rating (C0)	0,885 kN
(Grease) Lubrication Speed	34 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.008
EAN	4547359571325
Product Group	B00308
Enclosure	2 Metal Shields



Timken BEARING MFG.CORP

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	6MM Bore; 19MM Outside Diameter; 6MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	626ZZ/5C
Weight / LBS	0.018
Outer Race Width	0.236 Inch 6 Millimeter
Bore	0.236 Inch 6 Millimeter
Outside Diameter	0.748 Inch 19 Millimeter
bore diameter:	6 mm
static load capacity:	885 N
outside diameter:	19 mm
precision rating:	ISO Class 0
overall width:	6 mm
finish/coating:	Uncoated
bore type:	Round



Timken BEARING MFG.CORP

bearing material:	High Carbon Chrome Steel
closure type:	Double Shielded
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	6 mm
snap ring included:	Without Snap Ring
outer ring width:	6 mm
internal clearance:	CN
maximum rpm (grease):	34000 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	0.3 mm
dynamic load capacity:	2340 N
manufacturer product page:	Click here